INTERFACES & MIXED-SIGNAL

Garmo Morphic PHY (GMPHY)

Training; measurement; dual-path RX; profile switching; health; failover; analog primitive API

IP-088 · Architecture IP · Architecture

Function and architecture

- Training
- measurement
- dual-path RX
- profile switching
- health
- failover
- analog primitive API

Integration summary

Garmo Morphic PHY (GMPHY) integration role: Adaptive self-instrumenting PHY engine. Documented composition: Training; measurement; dual-path RX; profile switching; health; failover; analog primitive API.

Technical record

Canonical identity	IP-088
Responsibility	Adaptive self-instrumenting PHY engine
Documented building blocks	Training; measurement; dual-path RX; profile switching; health; failover; analog primitive API
Delivery boundary	Architecture
Evidence scope	Architecture IP

Delivery and release binding

- Interface version and parameter set
- Clock/reset domains and integration constraints
- Companion memory, PHY and software requirements
- Verification collateral and acceptance criteria

Confirm for the selected release: Node/library binding, Clock/reset limits, Physical and protocol dependencies, Artifact hashes, Acceptance criteria.

Evidence and qualification

Canonical technology and its architecture/integration role are recorded. The offered delivery is confirmed against the exact release before licensing.

No node-port, silicon-performance, standards certification or analog qualification is inherited from a related product.

Canonical status: Engineering build-spec

Evaluation and licensing

Evaluation: Evaluate an individual IP configuration. Production: Named-design production license. Custom work: Node binding or derivative integration. Rights, pricing, support and acceptance criteria are agreed for the exact scope.

Contact: patrick@garmolabs.com | Product path: /ip/garmo-morphic-phy-gmphy